

# SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: [www.summittelecomm.com](http://www.summittelecomm.com)

E-mail: [sales@summittelecomm.com](mailto:sales@summittelecomm.com)

[summittelecomm@hotmail.com](mailto:summittelecomm@hotmail.com)



## Disconnection Module

Item Code:STDM-10PT

### 10 Pair Disconnection Module with Screw Terminal



We are China leading manufacturer provides 10 Pair Disconnection Module With Screw Terminal, Krone Seires Module, FT Module, High Band Module and so on.

#### Description:

10 Pair Disconnection Module is used in telecommunication field for terminating wire cable of telephone communication. It can be used in Main Distribution Frame or Distribution Box.

#### Features:

- 10 pair disconnection module on cable side with an additional screw terminal, for terminating wires with conductor cross section up to 2.5mm<sup>2</sup>
- The design of contacts basing on the principle of airtight contacting makes a completely reliable connection between the contacts and wires
- Material of Plastic Parts: PBT/ABS/PC, Fire-Resistant
- Material of Contacts Pin: Silver/Tin Plated Phosphor Bronze
- Color: White base with White body.

**Technical Specifications:**

- Internal diameter of connection wire:0.4-0.7 mm
- External diameter of connection wire (shield):0.7-1.4 mm
- Insulation resistance: 1,000m $\Omega$  / 500V (DC).
- Typical contact resistance of wire connection approx  $R < 0.007\text{ohm}$ .
- Voltage intensity:1000V/min without breakdown and arcover