

SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: www.summittelecomm.com

E-mail: sales@summittelecomm.com

summittelecomm@hotmail.com



Disconnection Module
Item Code:STDM-10PG

10 Pair Krone Wire Guide Disconnection Module



We are China leading manufacturer provides 10 Pair Wire Guide Disconnection Module, Krone Series Module, FT Module, High Band Module, Earth Module and so on.

Features:

- 10 Pair Krone Disconnection Module, Wire Guide Type Module.
- The 10 Pair Disconnection Module is compatible with Krone LSA-PLUS 10-Pair Disconnection Module.
- 10 Pair Krone Disconnection Module Wire Guide.
- The design of contacts basing on the principle of airtight contacting makes a completely reliable connection between the contacts and wires
- Material of Plastic Parts: PBT/ABS/PC, Fire-Resistant
- Material of Contacts Pin: Silver/Tin Plated Phosphor Bronze
- Color: Gray base with white body

Technical Specifications:

- Internal diameter of connection wire: 0.4-0.7 mm
- External diameter of connection wire (shield): 0.7-1.4 mm

- Insulation resistance: 1,000m Ω / 500V (DC).
- Typical contact resistance of wire connection approx $R < 0.007\text{ohm}$.
- Voltage intensity: 1000V/min without breakdown and arcover