

SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: www.summittelecomm.com

E-mail: sales@summittelecomm.com

summittelecomm@hotmail.com



Other Connectivity Hardware

Item Code: ST110C

110 Connector



110 PCB Connector



Summit Telecom is China leading manufacturer provides 110 IDC Connector, 110 Termination Connecting Block, 110 Wiring Block and other modules.

Features:

- Colored component combinations for convenience of identification and network management
- Material of Plastic Parts: PC UL94v-0 or UL94V-2
- IDC specification: IDC contact material: phosphor bronze with gold/silver plating over nickel
- Contact material: phosphor bronze with (3-50 MIC) gold plating over nickel
- Cable fit: 22/24/26 AWG (0.4mm, 0.5mm, 0.6mm)

Technical Specification

- Plug: at least 30lbs (between plug and jack)
- Repetitive use: min. 700 times
- Surface plastic with pressure and combustion resisting function
- Terminal and connection patch material: cuprum phosphorus alloy
- Insulation voltage is 1,000V 60Hz (1min)
- Insulation resistance: min. 10M Ω
- Contact resistance: max. 20M Ω
- Grade of electric current is 1.5A (20 $^{\circ}$ C)
- Applicable temperature:
 - 40 ~ 70 $^{\circ}$ C (stored)
 - 10 ~ 60 $^{\circ}$ C (working)
- Relative humidity when operating: max. 93%