

SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: www.summittelecomm.com

E-mail: sales@summittelecomm.com

summittelecomm@hotmail.com



Copper Cable Splice Closure and Connector Item Code: STCAC

Aerial Copper Cable Closure



Summit Telecom is China leading manufacturer provides Aerial Closure,Copper Cable Closure,Splicing Module,etc. in outside copper cable splicing.

Features:

- Aerial Closures are designed for new build or maintenance applications. The one piece free breathing construction provides an excellent housing for cable splices in the harshest of environments.
- Free breathing and suitable for straight, butt and branch splices of non-pressurised communication cables

- Material: High-density polyethylene, strong and durable
- The closure consists of three main components: a central body and two end pieces.
- The end pieces provide a quick and easy method of installing cables, and limit water in. Cable supports can also be provided.
- After splice preparation and bonding, two closure end pieces are placed over the cable. The central body is then closed over the end pieces and the splice to provide a secure cover. The body is locked in place by bolts along its bottom (metal latches are available).
- Suitable for splicing module and UY,UG connector.

Technical Specifications:

- Environment Temperature: -40°C - $+60^{\circ}\text{C}$;
- Environment Atmosphere: 80—106Mpa;
- Relative Humidity: $\leq 95\%$;

	Specifications			
Connection Max Diameter	45	56	66	91
Main Cable Diameter(mm)	5-18	5-25	5-30	5-41
Branch Cable Diameter(mm)	5-8	5-15	5-15	5-25
Connection Port Distance(mm)	250	356	493	533
Size(D*L)	$\phi 60 \times 350$	$\phi 80 \times 480$	$\phi 90 \times 560$	$\phi 117 \times 660$
Continuity Cable	D0.4—40 Pair	D0.4—150 Pair	D0.4—400 Pair	D0.4—600 Pair
	D0.5—10 Pair	D0.5—70 Pair	D0.5—200 Pair	D0.5—400 Pair