

# SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: [www.summittelecomm.com](http://www.summittelecomm.com)

E-mail: [sales@summittelecomm.com](mailto:sales@summittelecomm.com)

[summittelecomm@hotmail.com](mailto:summittelecomm@hotmail.com)



## Fiber Optic Splice Closure

Item Code: GJS-FOSC221

### Fiber Generic Closure Organizer 288 Core,High Capacity



We are China leading manufacturer for Fiber Generic Closure Organizer 288 Core,High Capacity Fiber Splice Closure to meet requirements to capacity.

#### Description:

- The closure casing is made of quality engineering plastics, and of good performance of anti-erosion against acid and alkali salt, anti-aging, as well as reliable mechanical structure to make sure the closure service life. The mechanical structure is reliable and has the performance of resisting wild environment and intensive climate changes and serious working environment. The protection grade reaches IP66.
- The closures are applicable to ribbon type optical cable and common optical cable.

The splice trays inside the closure are turn-able like booklets, and have adequate curvature radius and space for winding optical fiber to make sure the curvature radius for optical winding 40mm. Each optical cable and fiber can be operated individually.

- The closure is of small volume, big capacity and convenient maintenance. Capacity up to 576 core for ribbon cable.
- The elastic rubber seal rings inside the closure are of good sealing and sweat-proof performance. The casing can be opened repeatedly without air leakage. No special tools are required. The operation is easy and simple.
- Compatible with most cable types (single fiber or ribbon) and cable constructions (loose tube, central core, slotted core)
- Typically used for customer drops, tap-offs (taut sheath) and in-line splice applications.
- The scope of application is: aerial, underground, pipeline, hand-holes.
- 6~8 ports for cable inlet/outlet.
- Capacity: 24 core for 1 tray, maximum 12 pcs trays installed up to 288 core.
- Sealing Type: Heat Shrink.

#### **Operation conditions:**

---

- Temperatures:  $-40^{\circ}\text{C} \sim +65^{\circ}\text{C}$
- Humidity:  $\leq 95\%$  (at  $40^{\circ}\text{C}$ )
- Air Pressure: 70kPa ~106kPa

#### **Technical Specifications:**

---

- Seal performance: after the box is sealed, inflate to 100kPa inwards (inflation only apply to the models with the air hole), and then soak it in the water of normal temperature, after 15 minutes of steady observation, there is no bubble to overflow.
- Insulation resistance: the insulation resistance between the metal work piece and the earth is greater than 20kM $\Omega$ .
- Pressurization: there is no breakdown or flashover under 15kVdc/1min between the metal work piece and the earth.
- The curvature radius of the fiber 40mm, without extra loss inside the splice tray.
- It can bear the axial tensile strength no less than 1000N.
- Lifetime: 30 years.