

SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED


Web: www.summittelecomm.com

E-mail: sales@summittelecomm.com
summittelecomm@hotmail.com




Fiber Optic Connection Components Item Code:STAP

Fiber Optic Armoured Pigtail



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011



Description:

Summit Telecom is a China leading manufacturer for Fiber Optic Armoured Pigtail, which are with stainless steel tube inside the outer jacket to protect the central unit of the cable. So they will not get damage even they are stepped by an adult and bit by rodents.

Features:

- Armoured Pigtail, Fiber Optic Armoured Pigtail.
- 600µm tight buffer fiber, steel tube protection, aramid yarn and reinforcing steel-wire braiding flame-retardant jacket
- High indentation strength, high tensile strength and gopher protected
- Small diameter, flexibility and easy bending
- Excellent stripping performance of tight buffer fiber
- Suited to SM fiber and MM fiber (50µm and 62.5µm)
- Ideal for fiber optic temperature transmission project
- Mini armored-protection
- High pull & pressure endurance
- Prevent bite by rodents
- Torsion damage resistance
- Strong and flexible, easy to use
- Could be Ordered as Customer Special Request as: UV, VO Protection for the Box, Good Screw Up to 40N, Filled with Silicon Gelly.

Application:

- Telecommunications
- CATV, LAN, MAN, WAN, Test & Measurement
- Military industry
- Medical

Technical Specifications:

Parameter & Specification	
Mode	Single-mode ,Multi-mode
Type	FC,LC,SC,ST,MU,MTRJ,MPO,E2000
Polishing	APC,UPC,PC
Insertion Loss(dB)	≤0.2 , ≤0.3
Return Loss(dB)	≥50, ≥65
Exchangeability(dB)	≤0.2
Repeatability(db/1000times)	≤0.2
Operation Wavelength(nm)	850,1310,1550
Operating Temperature(°C)	-30 ~ +75

Storage Temperature (°C)	-40 ~ +85
Cable OD(mm)	0.9 ,2.0 ,3.0
Cable Material	OFNR LDZH&Polarization maintaining..