

SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: www.summittelecomm.com

E-mail: sales@summittelecomm.com
summittelecomm@hotmail.com



FTTH Fiber Optic Cables
Item Code: STFFC-GJYXCH

GJYXCH Self Supporting Bow-type Drop Cable



NINGBO SUMMIT TELECOM CO.,LTD ALL RIGHTS RESERVED 2012



NINGBO SUMMIT TELECOM CO.,LTD ALL RIGHTS RESERVED 2012

Description

GJYXCH self supporting bow-type drop cable:optical fiber(s) is placed between two steel wire strength members, with self-supporting steel wire strength component,low smoke, non-halogen flame retardant outer sheath material.

Features

- Can adopt the slight bending resistant fiber B6,ensure data transmission.
- Small size, light weight, simple structure, easy to strip for its special groove design and no need any tool, easy to install.
- Two parallel phosphated steel wire as strength member have excellent crush and tensile resistance.
- Self-supporting steel wire strength component withstand most part of tension.
- low smoke, non-halogen flame retardant outer sheath material.

Applications

- Applicable as drop cable access to FTTH,FTTO,FTTB network,etc.
- Laying way:overhead,pipeline.
- Operating Temperature: -20~+ 50℃

Technical Specifications

No. of cores	Fiber	Outer diameter (mm)	Weight (kg/km)	Tensile force (N)		flattening force (N)		Minimum bending radius (mm)	
				Transient	Long	Transient	Long	Static	Dynamic
1	B1	2.0×5.0	21.5	≥600	≥300	≥2200	≥1000	30	60
	B1.3							30	60
	B6a							15	30
	B6b							10	25
2	B1	2.0×5.0	21.5	≥600	≥300	≥2200	≥1000	30	60
	B1.3							30	60

	B6a							15	30
	B6b							10	25
4	B1	2.0×5.0	21.5	≥600	≥300	≥2200	≥1000	30	60
	B1.3							30	60
	B6a							15	30
	B6b							10	25