SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED Web: <u>www.summittelecomm.com</u> E-mail: <u>sales@summittelecomm.com</u> <u>summittelecomm@hotmail.com</u>



Disconnection Module Item Code: STHBM

Krone High Band Disconnection Module

10 Pair High Band Module



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011

10 Pair High Band Profile Module



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011

8 Pair High Band Profile Module



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011

Description:

10 Pair/8 Pair Krone High Band Disconnection Module,10 Pair/8 Pair Cat5e Module can privde superior high speed data and voice cross connect, enables high speed LAN and WAN systems maximum headroom in transmission performance.

Features:

- The design of contacts basing on the principle of airtight contacting makes a completely reliable connection between the contacts and wires
- Material of Plastic Parts:PBT/ABS, Fire-Resistant
- Material of Contacts Pin: Silver/Tin Plated Phosphor Bronze
- Color:Gray base with white body.

Technical Specifications:

- Suitable diameter: 0.4 0.6mm
- Durability: 200 cycles
- Intermediate resistance: no more than 2.5mΩ in normal atmosphere pressure(not including bulk resistor).
- Insulated resistance: no less than 1,000MΩ in normal atmosphere pressure
- The intensity of anti-currency: DC 1,000V (AC, 700V), no puncture and flash-over phenomenon in one minute. In accordance with industry standard

Order Information:

- 10-pair High Band Disconnection Module
- 10-pair Profile High Band Disconnection Module
- 8-pair Profile High Band Disconnection Module