

# SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: [www.summittelecomm.com](http://www.summittelecomm.com)

E-mail: [sales@summittelecomm.com](mailto:sales@summittelecomm.com)

[summittelecomm@hotmail.com](mailto:summittelecomm@hotmail.com)



## Disconnection Module

Item Code:STDM STCM

### Krone Disconnection/Connection Module LSA-PLUS LSA-Profile



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011

**Description:**

Krone Disconnection/Connection Module is used in telecommunication field for terminating wire cable of telephone communication. It can be used in Main Distribution Frame or Distribution Box.

**Features:**

- The design of contacts basing on the principle of airtight contacting makes a completely reliable connection between the contacts and wires
- Material of Plastic Parts: PBT/ABS/PC, Fire-Resistant
- Material of Contacts Pin: Silver/Tin Plated Phosphor Bronze
- Color: many colors available as pictures show.

**Specifications:**

- Internal diameter of connection wire: 0.4-0.7 mm
- External diameter of connection wire (shield): 0.7-1.4 mm
- Insulation resistance: 1,000m $\Omega$  / 500V (DC).
- Typical contact resistance of wire connection approx  $R < 0.007\text{ohm}$ .
- Voltage intensity: 1000V/min without breakdown and arcover

**Order Information:**

5-pair Disconnection Module  
5-pair Connection Module  
8-pair Disconnection Module  
8-pair Connection Module  
10-Pair Disconnection Module  
10-Pair Connection Module  
10-Pair Profile Disconnection Module  
10-Pair Profile Connection Module  
10-pair Switch Module