SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: www.summittelecomm.com E-mail: sales@summittelecomm.com summittelecomm@hotmail.com



Disconnection Module Item Code:STSM

Krone LSA-IDC Switching Module LSA-Plus LSA-Profile



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011



We are China leading manufacturer provides 10 Pair 8 Pair Krone LSA-IDC Switching Module, Krone Seires Module, FT Module, High Band Module and so on.

Description:

10 Pair and 8 Pair Switching Modules, Krone LSA-IDC Switching Modules are used in telecommunication field for terminating wire cable of telephone communication. It can be used in Main Distribution Frame or Distribution Box, mount onto 2/10 back mount frame or 2/8 back mount frame.

Features:

- The design of contacts basing on the principle of airtight contacting makes a completely reliable connection between the contacts and wires
- Material of Plastic Parts:PBT/ABS, Fire-Resistant
- Material of Contacts Pin: Silver/Tin Plated Phosphor Bronze
- Color:Gray base with red body.

Techinical Specifications:

- Internal diameter of connection wire:0.4-0.7 mm
- External diameter of connection wire (shield):0.7-1.4 mm
- Insulation resistance: 1,000mΩ / 500V (DC).
- Typical contact resistance of wire connection approx R<0.007ohm.
- Voltage intensity:1000V/min without breakdown and arcover

Order Information:

10-pair Switch Module8-pair Switch Module10-pair Profile Switch Module8-pair Profile Switch Module