

---

# SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

Web: [www.summittelecomm.com](http://www.summittelecomm.com)

E-mail: [sales@summittelecomm.com](mailto:sales@summittelecomm.com)

[summittelecomm@hotmail.com](mailto:summittelecomm@hotmail.com)



---

## Communication Cables

Item Code: STLCC

### Local Communications Cables

#### Description

Transmitting audio frequency signals, analog signals up to 150kHz or digital signals up to 2048kbit/s and in certain condition can carry digital signals which is higher than 2048kbit/s. The product is suitable for the communication lines in town, outskirts and local areas. It is designed for aerial/duct/burial use in exchange area service.

#### Types

HYA、HYAC、HYAT、HYAT53、HYA53、HYA553、HYAT553。

#### Description(for broadband applications)

The product is suitable for transmitting system of long-distance optical network cell and subscriber, or subsystem as connection between floor and floor in integrated wiring system of buildings. Transmitting frequency (Max.): 30MHz or 100MHz.

#### Types

HSYA-30/100 HSYAC-30/100 HSYAT-30/100 HSYA53-30/100 HSYAT53-30/100

#### Part products introduction

- HYA (Duct/Aerial)

Conductor diameter (mm): 0.32、0.40、0.50、0.60、0.70、0.80、0.90

Size (Pairs): 5—3000

HSYA-30/100

Conductor diameter (mm): 0.50、0.60、0.90

Size (Pairs): 4---200



PE Sheath  
Dual sided plastic-coated aluminum tape  
Non-hygroscopic dielectric tape  
Core

- HYAC ( Aerial)


Conductor diameter (mm) : 0.40、0.50、0.60、0.63、0.70、0.80、0.90

Size (Pairs): 10—300

HSYAC-30/100

Conductor diameter (mm): 0.50、0.60、0.90

Size (Pairs): 4---200



Steel messenger  
PE Sheath  
Dual sided plastic-coated aluminum tape  
Non-hygroscopic dielectric tape  
Core

- HYAT (Prevents the entrance of water)


Conductor diameter (mm): 0.32、0.40、0.50、0.60、0.63、0.70、0.80、0.90

Size (Pairs): 10—1600

HSYAT-30/100

Conductor diameter (mm): 0.50、0.60、0.90

Size (Pairs): 4---200



PE Sheath  
Dual sided plastic-coated aluminum tape  
Non-hygroscopic dielectric tape  
Core (Filled with oil grease)

- HYA53/HYAT53 (Rodent-proof/ Direct burial)


Conductor diameter (mm): 0.40、0.50、0.60、0.70、0.80、0.90

Size (Pairs): HYA53 10—2400 HYAT53 10—600

HSYA53/HSYAT53-30/100

Conductor diameter (mm): 0.50、0.60、0.90

Size (Pairs): 4---200




PE外护套	PE Over sheath
单层钢带铠装	Single steel tape armor
PE护套	PE Sheath
铝塑复合带	Dual sided plastic-coated aluminum tape
包带	Non-hygroscopic dielectric tape
缆芯 (T型充油)	Core ( TypeT Filled with oil grease)

● HYA553/HYAT553 (Rodent-proof/ Direct burial)

Conductor diameter (mm): 0.40、0.50、0.60、0.70、0.80、0.90

Size (Pairs): HYA553 10—2400 HYAT553 10—600



PE外护套	PE Over sheath
双层钢带铠装	Double steel tape armor
PE护套	PE Sheath
铝塑复合带	Dual sided plastic-coated aluminum tape
包带	Non-hygroscopic dielectric tape
缆芯 (T型充油)	Core ( TypeT Filled with oil grease)