SUMMIT TELECOM

©2013 SUMMIT TELECOM ALL RIGHTS RESERVED

 $Web: \underline{www.summittelecomm.com}$

E-mail: sales@summittelecomm.com
summittelecomm@hotmail.com



Copper Cable Splice Closure and Connector Item Code: STCSC

UY UY2 UR UR2 U1B U1R Wiring Connector



NINGBO SUMMIT TELECOM ALL RIGHTS RESERVED 2011

Summit Telecom is China leading manufacturer provides UY UY2 UR UR2 U1B U1R Wiring Connector, Splicing Module, Aerial Closure, etc.

Features:

- The product application is for "Jointing of Telephone Cables in the Telephone Network" and demands high quality performance. The cables are laid either Underground or Aerial.
- Two wire inline joints on telephone drop wire of phosphor bronze with plated tin conductors, which will be suitable for crimping tool shown.
- All materials is suitable for operation in the tropic with maximum temperature up to 8 0°C.
- All materials used in the connectors shall be non-toxic and dermatologically safe.
- Connectors can retain the electrical & mechanical properties in the test report over w orking temperature range -30°C to 70°C and humidity range of 0% to 95%.
- Gel filled and gas tight, the UY2 butt connector and UB2A splice connector are widely
 used in the telecoms industry and other fine wire applications. Wires are simply
 inserted into the housing and crimped down which actuates an insulation
 displacement mechanism automatically connecting the two wires into an
 environmentally gel sealed unit.

Technical Specifications:

Maximum insulation	Wire Range	Item Name
1.52mm	0.4-0.7mm	UY
2.08mm	0.4-0.9mm	UY2
1.67mm	0.4-0.9mm	UR
2.08mm	0.4-0.9mm	UR2
3.18mm	0.9-1.3mm	U1B
3.18mm	0.5-0.9mm	U1R

Order Information:

UY Connector—STCSC-UY

UY2 Connector—STCSC-UY2

UR Connector—STCSC-UR

UR2 Connector—STCSC-UR2

U1B Connector—STCSC-U1B

U1R Connector—STCSC-U1R